



Yuasa Technisches Datenblatt

Yuasa YBX3102 - YBX3000 SMF Batteries

Leistung

Spannung	12V
Kapazität 20 Std	40Ah
Kaltstartstrom (A) EN1	360A

Abmessungen

Länge	175mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Mean Weight with Acid	10.5kg
Gewicht (trocken)	-
Säure Volumen	-



Gehäuseeigenschaften

Gehäusotyp	L0 DIN
Cell Layout	1
Batteriehälter	B3
Ladezustandsanzeige	✓
Tragegriffe	✓
Entgasung	✓
Semi Traktionseigenschaften	-
Deckel Typ	SMF Double Lid

Technologie

Flammschutz	✓
Technologie	Ca/Ca
Separator	PE
VDA Überroll Test	✓
Vibration	V1 (30Hz/3g/2hr)
Ladestrom	2A

Anschlusspol Typ

Zellenanordnung

Batteriehälter

T1

Standard DIN Post



Ausstellungsdatum: 12/05/2016 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX3102 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	40Ah
Cold Cranking Amps (EN1)	360A

Dimensions

Length	175mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	10.5kg
Dry Weight	-
Acid Volume	-



Container Features

Case Type	L0 DIN
Cell Layout	1
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Semi-Traction Features	-
Lid Type	SMF Double Lid

Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Vibration	V1 (30Hz/3g/2hr)
Recommended Charge Rate	2A


Terminal Type

Cell Assembly Layout

Battery Hold-down

T1

Standard DIN Post



Data Sheet generated on 12/05/2016 - E&OE