



## Yuasa Technisches Datenblatt

### Yuasa YBX3068 - YBX3000 SMF Batteries

#### Leistung

Spannung	12V
Kapazität 20 Std	70Ah
Kaltstartstrom (A) EN1	570A

#### Abmessungen

Länge	269mm
Breite	174mm
Höhe	225mm

#### Maße und Gewichte

Mean Weight with Acid	17.3kg
Gewicht (trocken)	-
Säure Volumen	-



#### Gehäuseeigenschaften

Gehäusotyp	JIS D26 + B9
Ladezustandsanzeige	✓
Tragegriffe	✓
Entgasung	✓
Semi Traktionseigenschaften	-
Deckel Typ	SMF Double Lid


#### Technologie

Flammschutz	✓
Technologie	Ca/Ca
Separator	PE
VDA Überroll Test	✓
Vibration	V1 (30Hz/3g/2hr)
Ladestrom	4A

#### Anschlusspol Typ

##### T1


Standard DIN Post



Positive Terminal

Negative Terminal


#### Zellenanordnung



0

#### Batteriehalter

B9



Ausstellungsdatum: 12/05/2016 - E&EO



## Yuasa Technical Data Sheet

### Yuasa YBX3068 - YBX3000 SMF Batteries

#### Performance

Voltage	12V
Capacity (20-hour)	70Ah
Cold Cranking Amps (EN1)	570A

#### Dimensions

Length	269mm
Width	174mm
Height	225mm

#### Weights & Measures

Mean Weight with Acid	17.3kg
Dry Weight	-
Acid Volume	-



#### Container Features

Case Type	JIS D26 + B9
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Semi-Traction Features	-
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Vibration	V1 (30Hz/3g/2hr)
Recommended Charge Rate	4A

#### Terminal Type

##### T1


Standard DIN Post




Positive Terminal

Negative Terminal

#### Cell Assembly Layout



#### Battery Hold-down



Data Sheet generated on 12/05/2016 - E&OE